

SPECIFICATIONS

EXITS

HOUSING

- Extruded aluminum housing
- White powdercoat finish standard, black and aluminum finishes also available
- Field selectable knockout chevron directional indicators
- Unit can be ordered as single (1), double (2), or single/double (3) face applications

ELECTRICAL

- Dual 120/277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C - 45°C (50°F - 113°F)
- Less than 2W power consumption

ILLUMINATION

- Ultra bright, energy efficient red or green LEDs

BATTERY

- Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours
- 120 Minute battery also available

MOUNTING

- Mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount

CODE COMPLIANCE

- cSAus Listed for Indoor Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title20 Certified
- BAA Compliant

WARRANTY

- 5 Year



EA
Extruded Aluminum Exit

ORDERING INFORMATION

MODEL#	Face #	Letter	Housing
EA	1	R (Red)	W (White)
	2	G (Green)	B (Black)
	3		A (Aluminum)

Options (Factory Installed)

EM	- NiCad Battery
EM2	- 120 Minute NiCad Battery
SD	- Self Diagnostics (requires EM)
2AC	- Dual Circuit (AC only)
FA	- Fire Alarm Interface (specify type - open/closed dry contact)
IV	- Visual Intermittent Alarm (requires EM-SD)
TPS	- Tamper Proof Screws
SWXE	- Special Wordng Panel (prefix to part number)

Accessories (Ships on Side)

WG18	- Wire Guard
SK12-W	- 12" Pendant Kit - White
SK12-B	- 12" Pendant Kit - Black
SK12-BA	- 12" Pendant Kit - Brushed Aluminum

