



Project

Type

Catalog Number

**SPECIFICATIONS**

**EXITS**

**HOUSING**

- Extruded aluminum housing
- Available in aluminum, white, or black finishes
- Unit can be surface or recessed mounted, field selectable
- Exits come with single and double face configurations, field selectable
- Chevron indicators are field selectable

**ELECTRICAL**

- Dual 120/277V standard
- Charge rate/power "On" LED light and push-to-test switch for testing
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- 3W or less energy consumption on AC models, 5W or less on EM models

**ILLUMINATION**

- Ultra bright, energy efficient red or green LEDs
- Clear or silver mylar acrylic panels

**BATTERY**

- Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

**MOUNTING**

- Unit can be surface wall, ceiling, sloped ceiling, or end mount
- Can also be recessed wall, ceiling, sloped ceiling mount

**CODE COMPLIANCE**

- UL Listed for Damp Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title20 Certified

**WARRANTY**

- 5 Year



**EDG-UN**  
**Universal Edgelit Exit**

**ORDERING INFORMATION**

MODEL#	# Faces / Panel	Housing
EDG-UN	R1 (Red - 1 Face Clear and 2 Face Mirror Panel)	A (Aluminum)
	R2 (Red - 1 Face Mirror and 2 Face Mirror Panel)	W (White)
	G1 (Green - 1 Face Clear and 2 Face Mirror Panel)	B (Black)
	G2 (Green - 1 Face Mirror and 2 Face Mirror Panel)	

EX: EDG-UN-R2-A

**Options (Factory Installed)**

- EM - NiCad Battery
- SD - Self Diagnostics (requires EM)

**Accessories (Order Separately, Ships on Side)**

- EDG-UN-SK12-\* - 12" Pendant Kit
- EDG-UN-SK24-\* - 24" Pendant Kit
- EDG-E-PA - Pendant Adapter

\*Specify **W-White**, **B-Black**, **BA-Aluminum**

