

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Aluminum housing
- Available in aluminum, white, or black
- Can be ordered in single, double, or universal face configurations
- Chevron indicators are field selectable

ELECTRICAL

- Dual 120/277V standard
- Operating Temperature: 0°C - 50°C (32°F - 122°F)

ILLUMINATION

- Red LEDs

BATTERY

- Maintenance free NiCad battery available
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Universal knockout pattern on back plate for wall mounting
- Aluminum canopy included for top or end mount

CODE COMPLIANCE

- UL Listed for Damp Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title 20 Compliant

WARRANTY

- 5 Year

ORDERING INFORMATION

| MODEL# | # Faces | Letter | Housing | Face |
|--------|---------|---------|--------------|--------------|
| NYCA | 1 | R (Red) | A (Aluminum) | A (Aluminum) |
| | 2 | | W (White) | W (White) |
| | 3 | | B (Black) | B (Black) |

OPTIONS (Factory Installed)

- EM - NiCad Battery
- SD - Self Diagnostics
- 2C - Dual Circuit (AC only)



**NYCA
NYC Approved
Cast Aluminum Exit**

