



Project

Type

Catalog Number

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Durable 20 gauge steel housing
- White powdercoat finish standard
- Removable chevrons standard
- Available in single or double face
- Specify between two or three lamp heads

ELECTRICAL

- Dual 120/277V
- Consumes less 2W or less
- Charge rate/power "On" LED light and push-to-test switch for testing
- Operating Temperature: 10°C - 40°C (50°F - 104°F)
- Heater Temperature: -20°C (4°F)

BATTERY

- Sealed Lead Acid Battery
- NiCad Battery also available (NI)
- Low Voltage Disconnect prevents battery from deep discharge
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Available as wall, ceiling, or end mount

CODE COMPLIANCE

- cSAus Listed for Wet Locations
- NEMA4X Listed
- Sanitation Listed
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- BAA Listed

WARRANTY

- 5 Year



**NYEX4XC
NYC Approved
NEMA4X Combo**

ORDERING INFORMATION

MODEL#	Face #	Letter	Housing	Mounting	Operation	Lamping
NYEX4XC	1 Single	R Red	W White	W Wall	6V12W 12V12W	See Chart
				C Ceiling	6V18W 12V27W	
	2 Double	R Red	W White	E End	6V22W-NI 12V36W	
					6V27W 12V42W-NI	
					6V36W 12V60W	
					6V42W-NI 12V72W	
					6V54W-NI 12V90W-NI	
					6V60W 12V120W	
					6V72W 12V140W	
					6V90W-NI	
	6V100W 24V120W					
				6V120W		

EX: NYEX4XC1RW-W-6V22-NI-RHS3-LMR05

LAMPING

LH - Less Heads

*MR06 - 6W MR16 Halogen Lamp - uses RHS heads (6V)

*MR10 - 10W MR16 Halogen Lamp - uses RHS heads (6V, 12V)

*MR12 - 12W MR16 Halogen Lamp - uses RHS heads (12V, 24V)

*MR20 - 20W MR16 Halogen Lamp - uses RHS heads (12V, 24V)

*MR35 - 35W MR16 Halogen Lamp - uses RHS heads (12V, 24V)

*MR50 - 50W MR16 Halogen Lamp - uses RHS heads (12V, 24V)

*LMR02 - 2W MR16 LED Lamp - uses RHS heads(12V)

*LMR05 - 5W MR16 LED Lamp - uses RHS heads(6V, 12V, 24V)

*LMR07 - 7W MR16 LED Lamp - uses RHS heads(6V, 12V, 24V)

*10WH - 10W Halogen Lamps - PAR36 or RHS heads (6V)

*12WH - 12W Halogen Lamps - PAR36 or RHS heads (6V, 12V, 24V)

*20WH - 20W Halogen Lamps - PAR36 or RHS heads (6V, 12V, 24V)

*35WH - 35W Halogen Lamps - PAR36 or RHS heads (12V)

*50WH - 35W Halogen Lamps - PAR36 or RHS heads (24V)

*9W - 9W Incandescent Lamp - PAR36 or RHS heads(6V, 12V, 24V)

*12W - 18W Incandescent Lamp - PAR36 or RHS heads (12V)

*18W - 18W Incandescent Lamp - PAR36 or RHS heads (12V, 24V)

*Specify **RHW2/RHW3 (PAR36)** or **RHS2/RHS3 lamp heads**

OPTIONS (Factory Installed)

SD - Self Diagnostics

IA - Audible Intermittent Alarm

TD - Time Delay (specify voltage)

HTR - Internal Heater (specify voltage)

FPL - Food Prep Lens



ACCESSORIES (Order Separately)

WG9 - Wire Guard

SK12-* - 12" Stem Kit (other lengths available)

*Specify **W-White; B-Black; BA-Brushed Aluminum**

Single Face



Double Face

