

**SPECIFICATIONS**

**EXITS**

**HOUSING**

- 20-gauge steel housing
- Available in white or black finishes
- Field selectable knockout chevron directional indicators
- Unit can be ordered as single (1), double (2), or single/double (3) face applications

**ELECTRICAL**

- Dual 120/277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C - 40°C (50°F - 104°F)

**ILLUMINATION**

- Ultra bright, energy efficient red or green LEDs

**BATTERY**

- V Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

**MOUNTING**

- Mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount

**CODE COMPLIANCE**

- cSAus Listed for Damp Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title20 Certified
- BAA Compliant

**WARRANTY**

- 5 Year



**STXE-B**  
**Steel LED Exit**

**ORDERING INFORMATION**

MODEL#	# Faces	Letter	Housing
STXE-B	1	R (Red)	B (Black)
	2	G (Green)	W (White)
	3		

**Options (Factory Installed)**

EM	- NiCad Battery
EM2	- 120 Minute NiCad Battery
SD	- Self Diagnostics (requires EM)
2AC	- Dual Circuit (AC only)
FA	- Fire Alarm Interface (specify type - open/closed dry contact)
IA	- Audible Intermittent Alarm
IV	- Visual Intermittent Alarm (requires SD)
TPS	- Tamper Proof Screws
SWXE	- Special Wordng Panel (prefix to part number)

**Accessories (Order Separately, Ships on Side)**

SK12-W	- 12" Pendant Kit - White
SK12-B	- 12" Pendant Kit - Black
SK12-BA	- 12" Pendant Kit - Brushed Aluminum

