



Project

Type

Catalog Number

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Durable 20 gauge steel housing
- White powdercoat finish standard
- Black finish also available
- Removable chevrons standard
- Available in single, double, or universal face

ELECTRICAL

- Dual 120/277V
- Consumes less 2W or less
- Charge rate/power "On" LED light and push-to-test switch for testing
- Operating Temperature: 10°C - 45°C (50°F - 113°F)

BATTERY

- Optional maintenance free, NiCad battery available
- Low Voltage Disconnect prevents battery from deep discharge
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Universal knockout pattern on back plate
- Canopy provided

CODE COMPLIANCE

- cSAus Listed for Indoor Locations
- Meets UL Requirements
- BAA Compliant
- Meets Local and State Codes

WARRANTY

- 5 Year

ORDERING INFORMATION

CATALOG#	Face #	Letter	Housing
SWXEH-STXE-B-1RW	Single Face	Red	White
SWXEH-STXE-B-1GW	Single Face	Green	White
SWXEH-STXE-B-2RW	Double Face	Red	White
SWXEH-STXE-B-2GW	Double Face	Green	White
SWXEH-STXE-B-3RW	Universal Face	Red	White
SWXEH-STXE-B-3GW	Universal Face	Green	White

OPTIONS (Factory Installed)

B	- Black Housing (replaces W in part number)
CC	- Custom Color
EM	- NiCad Battery (90 minutes)
EM120	- NiCad Battery (120 minutes)
IA	- Audible Intermittent Alarm
IV	- Visual Intermittent Alarm (specify voltage)
TPS	- Tamper Proof Screws

ACCESSORIES (Order Separately, Ships on Side)

SK12-*	- 12" Stem Kit (other lengths available)
--------	--

*Specify **W-White**; **B-Black**; **BA-Brushed Aluminum**



SWXEH-ST
Massachusetts
Approved Steel Exit

