

SPECIFICATIONS

EXITS

HOUSING

- Extruded aluminum frame
- Painted extruded aluminum stencil
- Available in red, green, black, or brushed aluminum face plate
- Housing offered in white, black, bronze, or brushed aluminum finishes
- Universal chevrons

ELECTRICAL

- Requires no electricity or light source

ILLUMINATION

- 100ft visibility rating
- Light source consists of glass tubes which are internally coated with phosphor and filled with tritium gas (a natural hydrogen isotope)

BATTERY

- 10 or 20 year life span available
- Temperature Rating: -67°F - 176°F (-55°C - 80°C)

MOUNTING

- Surface wall mount standard
- Pendant kits available, sd well as bracket to top/end mount

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

WARRANTY

- 5 Year



TEX-BA
Self Luminous Exit
Aluminum Frame

ORDERING INFORMATION

MODEL#	Face #	Letters	Housing	Service Life (yrs)
TEX-BA	1	R (Red)	W (White)	10
	2	G (Green)	B (Black)	20
		B (Black)	Z (Bronze)	
		Z (Bronze)	A (Aluminum)	

Options (Ships Installed)

- SWXE - Special Wording (prefix to part number)
- VR - Vandal Resistant Lens (1/8" lens with TP screws)

Accessories (Order Separately, Ships on Side)

- MTB-I - Mounting Bracket for Top/End Mount
- SK12-I - 12" Pendant Kit
- SK24-I - 24" Pendant Kit
- SK36-I - 36" Pendant Kit
- SK48-I - 48" Pendant Kit
- WG-I-2 - Wireguard (14.0" x 10.0" x 4.5")
- WG-I-3 - Wireguard (14.5" x 6.0" x 10.5")
- WG-I-10 - Wireguard (13.5" x 12.0" x 16.5")

