

**SPECIFICATIONS**

**EXITS**

**HOUSING**

- Extruded aluminum frame
- Painted extruded aluminum stencil
- Available in red, green, black, or brushed aluminum face plate
- Housing offered in white, black, bronze, or brushed aluminum finishes
- Universal chevrons

**ELECTRICAL**

- Requires no electricity or light source

**ILLUMINATION**

- 100ft visibility rating
- Light source consists of glass tubes which are internally coated with phosphor and filled with tritium gas (a natural hydrogen isotope)

**BATTERY**

- 10 or 20 year life span available
- Temperature Rating: -67°F - 176°F (-55°C - 80°C)

**MOUNTING**

- Surface wall mount standard

**CODE COMPLIANCE**

- cULus Listed for Wet Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

**WARRANTY**

- 5 Year



**TEX-HA**  
**Vandal Resistant**  
**Aluminum Frame**  
**Self Luminous Exit**

**ORDERING INFORMATION**

MODEL#	Face #	Letters	Housing	Service Life (yrs)
TEX-HA	1	R (Red)	W (White)	10
		G (Green)	B (Black)	20
	2	B (Black)	Z (Bronze)	
		A (Aluminum)		

**Options (Ships Installed)**

SWXE - Special Wording (prefix to part number)

**Accessories (Order Separately, Ships on Side)**

WG-I-1 - Wireguard (17.0" x 17.0" x 7.0")  
 MT - Top/Surface Mount (comes standard with 2-face)

