

**SPECIFICATIONS**

**EXITS**

**HOUSING**

- ABS Plastic Frame
- Available in red, green, or black face plate
- Housing offered in white, black, or gray finishes
- Universal chevrons

**ELECTRICAL**

- Requires no electricity or light source

**ILLUMINATION**

- 100ft visibility rating
- Light source consists of glass tubes which are internally coated with phosphor and filled with tritium gas (a natural hydrogen isotope)

**BATTERY**

- 10 or 20 year life span available
- Temperature Rating: -67°F - 176°F (-55°C - 80°C)

**MOUNTING**

- Wall surface, pendant, or side mount

**CODE COMPLIANCE**

- cULus Listed for Wet Location
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

**WARRANTY**

- 5 Year



**TEX**  
**Self Luminous Exit**  
**Plastic Frame**

**ORDERING INFORMATION**

MODEL#	Face #	Letters	Housing	Service Life (yrs)
TEX	1	R (Red)	W (White)	10
	2	G (Green)	B (Black)	20
		B (Black)	G (Gray)	

**Options (Ships Installed)**

- SWXE - Special Wording (prefix to part number)
- VR - Vandal Resistant Lens (1/8" lens with TP screws)

**Accessories (Order Separately, Ships on Side)**

- SK12-I - 12" Pendant Kit
- SK24-I - 24" Pendant Kit
- SK36-I - 36" Pendant Kit
- SK48-I - 48" Pendant Kit
- WG-I-5 - Wireguard (15.75" x 14.75" x 6.75")

